

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**Trade name: **SPRAY 900 CAVITY WAX**

Article number: 199

1.2 Relevant identified uses of the substance or mixture and uses advised against

- Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- Product category PC9a Coatings and paints, thinners, paint removers
- Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
- Environmental release category ERC2 Formulation into mixture
- Article category AC1 Vehicles
- Application of the substance / the mixture
 - Surface protection
 - Underbody coating in a spray form

1.3 Details of the supplier of the safety data sheet**Manufacturer/Supplier:**

HB BODY S.A.
B' ENTRANCE BLOCK 50 DA9 & MB6 Str
THESSALONIKI INDUSTRIAL AREA
57.022, SINDOS
THESSALONIKI, GREECE
Ph: +30 2310 790 000
Fax: +30 2310 790 033
www.hbbody.com
email: hbbody@hbbody.com

Further information obtainable from:

HB BODY S.A.
B' ENTRANCE BLOCK 50 DA9 & MB6 Str
THESSALONIKI INDUSTRIAL AREA
57.022, SINDOS
THESSALONIKI, GREECE
Ph: +30 2310 790 000
Fax: +30 2310 790 033
www.hbbody.com
email: hbbody@hbbody.com

1.4 Emergency telephone number:

Regional Medicines and Poisons Information Centre NI
Pharmacy Department, Royal Hospital Suite
Grosvenor Road Belfast
Telephone: +44 28 90 63 2032
Fax: +44 28 90 24 80 30
Emergency telephone: 844 892 0111

E-mail address: nirdic.nirdic@belfasttrust.hscni.net

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

Trade name: **SPRAY 900 CAVITY WAX**

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



health hazard

STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.



STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

Low boiling point hydrogen treated naphtha

Naphtha (petroleum), hydrotreated light

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

H372 Causes damage to the central nervous system through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Trade name: SPRAY 900 CAVITY WAX**SECTION 3: Composition/information on ingredients****3.2 Chemical characterisation: Mixtures**

Description: Mixture of hazardous substances listed below with nonhazardous additions.

Dangerous components:

CAS: 106-97-8	butane, pure	30-<35%
EINECS: 203-448-7	 Flam. Gas 1A, H220	
Index number: 601-004-00-0	 Acute Tox. 3, H331	
RTECS: EJ 4200000	Press. Gas (Comp.), H280	
CAS: 64742-82-1	Low boiling point hydrogen treated naphtha	15-<20%
EINECS: 265-185-4	 Flam. Liq. 3, H226	
Index number: 649-330-00-2	 STOT RE 1, H372; Asp. Tox. 1, H304	
Reg.nr.: 01-2119458049-33-0002	 STOT SE 3, H336	
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light	5-<10%
EINECS: 265-151-9	 Flam. Liq. 2, H225	
Index number: 649-328-00-1	 Asp. Tox. 1, H304	
Reg.nr.: 01-2119475514-35-0001	 Aquatic Chronic 2, H411	
	 Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	≥2.5-<5%
EINECS: 265-199-0	 Flam. Liq. 3, H226	
Index number: 649-356-00-4	 Asp. Tox. 1, H304	
Reg.nr.: 01-2119455851-35-0001	 Aquatic Chronic 2, H411	
	 Acute Tox. 4, H332; STOT SE 3, H335	
CAS: 75-28-5	isobutane	1-<5%
EINECS: 200-857-2	 Flam. Gas 1A, H220	
Index number: 601-004-00-0	Press. Gas (Comp.), H280	
RTECS: TZ 4300000		
CAS: 74-98-6	propane	1-<5%
EINECS: 200-827-9	 Flam. Gas 1A, H220	
Index number: 601-003-00-5	Press. Gas (Comp.), H280	
RTECS: TX 2275000		

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Generally the product does not irritate the skin.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

Continue on page 4

GB

Trade name: SPRAY 900 CAVITY WAX**5.3 Advice for firefighters**

Firefighters should always wear protective equipment and breathing apparatus when handling fire coming from these products

5.6 Fire and explosion Hazards**Special protective equipment and fire fighting procedures:**

Mouth respiratory protective device.

Firefighters should wear full protective flameproof clothing and self contained breathing apparatus for the firefighter if necessary. In the event of any fire try cool down the tanks with water spray. If possible do not allow the water used by firefighters to enter the drains or come in any contact with the water supply lines for the public. Always seek as appropriate.

Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.**Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Not required.**Further information about storage conditions:** Keep container tightly sealed.**7.3 Specific end use(s)** No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****106-97-8 butane, pure**

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1,3-diene)

Continue on page 5

GB

Trade name: SPRAY 900 CAVITY WAX

- Regulatory information WEL: EH40/2020
- Additional information: The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- Personal protective equipment:
- General protective and hygienic measures:
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
- Respiratory protection:
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact in work areas without heightened risk of injury (e.g. Laboratory) gloves made of the following material are suitable:
The breakthrough time of gloves is unknown for this product itself. The glove material that can be used is recommended on the basis of the different substances in the preparation.
- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:
Rubber gloves
- **Eye protection:**
Safety glasses



Tightly sealed goggles

- Body protection: Protective work clothing

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

- General Information
- Appearance:

Form:	Fluid
Colour:	According to product specification
- Odour: Characteristic
- Odour threshold: Not determined.
- pH-value: Mixture is non-soluble (in water).

Continue on page 6
GB

Trade name: SPRAY 900 CAVITY WAX

- Change in condition
 - Melting point/freezing point: Undetermined.
 - Initial boiling point and boiling range: -44.5 °C
- Flash point: < 0 °C
- Flammability (solid, gas): Not applicable.
- Autoignition temperature: 296 °C
- Decomposition temperature: Not determined.
- Ignition temperature: Product is not selfigniting.
- Explosive properties: Risk of explosion by shock, friction, fire or other sources of ignition.
- Explosion limits:
 - Lower: 1.5 Vol %
 - Upper: 8.5 Vol %
- Vapour pressure at 20 °C: 2 hPa
- Density at 20 °C: 0.12001 g/cm³
- Relative density: Not determined.
- Vapour density: Not determined.
- Evaporation rate: Not applicable.
- Solubility in / Miscibility with water: Fully miscible.
- Partition coefficient: n-octanol/water: Not determined.
- Viscosity:
 - Dynamic: Not determined.
 - Kinematic: Not determined.
- Solvent content:
 - Organic solvents: 45.7 %
 - VOC (EC) 400.0 g/l
 - Solids content (volume): 7.5 %
- **9.2 Other information** No further relevant information available.

*

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
 - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

*

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
 - Acute toxicity Based on available data, the classification criteria are not met.

Continue on page 7
GB

Trade name: SPRAY 900 CAVITY WAX

- LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Inhalative LC50/4 h >239 mg/l (rat)

106-97-8 butane, pure

Inhalative LC50/4 h 658 mg/l (rat)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6,800 mg/kg (rat)

Dermal LD50 >3,400 mg/kg (rab)

Inhalative LC50/4 h >10.2 mg/l (rat)

- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Additional toxicological information:
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure
May cause drowsiness or dizziness.
- STOT-repeated exposure
Causes damage to the central nervous system through prolonged or repeated exposure.
- Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information**12.1 Toxicity**

- Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

12.2 Persistence and degradability

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

- **12.3 Bioaccumulative potential** No further relevant information available.

- **12.4 Mobility in soil** No further relevant information available.

- Ecotoxicological effects:

- Remark: Harmful to fish

- Additional ecological information:

- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

12.5 Results of PBT and vPvB assessment

- PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
- vPvB: This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- **12.6 Other adverse effects** No further relevant information available.

Trade name: SPRAY 900 CAVITY WAX**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

· Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information**14.1 UN-Number**

· ADR, IMDG, IATA

UN1950

14.2 UN proper shipping name

· ADR

UN1950 AEROSOLS

· IMDG

AEROSOLS

· IATA

AEROSOLS, flammable

14.3 Transport hazard class(es)

· ADR



· Class

2.5F Gases.

· Label

2.1

· IMDG, IATA



· Class

2.1 Gases.

· Label

2.1

14.4 Packing group

· ADR, IMDG, IATA

Void

14.5 Environmental hazards:

· Marine pollutant:

No

14.6 Special precautions for user

· Hazard identification number (Kemler code):

Warning: Gases.

· EMS Number:

-

· Stowage Code

F-D,S-U

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre:

Category A. For AEROSOLS with a capacity above 1 litre:

Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

Continue on page 9

GB

Trade name: SPRAY 900 CAVITY WAX

- Segregation Code
SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.
- **14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**
Not applicable.
- Transport/Additional information:
 - ADR
 - Limited quantities (LQ) 1L
 - Excepted quantities (EQ) Code: E0
Not permitted as Excepted Quantity
 - Transport category 2
 - Tunnel restriction code D
 - IMDG
 - Limited quantities (LQ) 1L
 - Excepted quantities (EQ) Code: E0
Not permitted as Excepted Quantity
 - UN "Model Regulation": UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



GHS02 GHS07 GHS08

- Signal word Danger
- Hazard-determining components of labelling:
Low boiling point hydrogen treated naphtha
Naphtha (petroleum), hydrotreated light
- Hazard statements
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H336 May cause drowsiness or dizziness.
H372 Causes damage to the central nervous system through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P405 Store locked up.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Continue on page 10
GB

Trade name: SPRAY 900 CAVITY WAX

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
 - H220 Extremely flammable gas.
 - H225 Highly flammable liquid and vapour.
 - H226 Flammable liquid and vapour.
 - H280 Contains gas under pressure; may explode if heated.
 - H304 May be fatal if swallowed and enters airways.
 - H315 Causes skin irritation.
 - H331 Toxic if inhaled.
 - H332 Harmful if inhaled.
 - H335 May cause respiratory irritation.
 - H336 May cause drowsiness or dizziness.
 - H372 Causes damage to organs through prolonged or repeated exposure.
 - H411 Toxic to aquatic life with long lasting effects.
- Department issuing SDS: Department of Quality Control
- Contact:
 - HB BODY S.A
 - Ms Olympia Stamkou
 - Ph: +30 2310 790 032
 - fax: +30 2310 790 033
 - email: stamkou@hbbody.com
- * Data compared to the previous version altered.

Trade name: SPRAY 900 CAVITY WAX

*

Annex: Exposure scenario 1**Short title of the exposure scenario**

- Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- Product category PC9a Coatings and paints, thinners, paint removers
- Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
- Article category AC1 Vehicles
- Environmental release category ERC2 Formulation into mixture

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

Conditions of use According to directions for use.

- Duration and frequency Frequency of use:

Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- Physical state Aerosol

- Concentration of the substance in the mixture The substance is main component.

- Used amount per time or activity Smaller than 100 g per application.

Other operational conditions

- Other operational conditions affecting environmental exposure Use only on hard ground.

- Other operational conditions affecting worker exposure

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- Other operational conditions affecting consumer exposure

No special measures required.

Keep out of the reach of children.

- Other operational conditions affecting consumer exposure during the use of the product Not applicable.

Risk management measures

- Worker protection

- Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

- Technical protective measures

Provide explosion-proof electrical equipment.

Use product only in enclosed systems.

Ensure that suitable extractors are available on processing machines

- Personal protective measures The usual precautionary measures are to be adhered to when handling chemicals.

- Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

Keep locked up and out of the reach of children.

- Environmental protection measures

- Water

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Do not allow to reach sewage system.

- Soil

Prevent contamination of soil.

The product is only processed over the concrete collecting basin.

- **Disposal measures** Ensure that waste is collected and contained.

Continue on page 12

GB

Trade name: SPRAY 900 CAVITY WAX· **Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging· **Exposure estimation**· **Consumer**

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

· **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

GB

Continue on page 13

Trade name: SPRAY 900 CAVITY WAX

*

Annex: Exposure scenario 2**Short title of the exposure scenario**

Product category PC9b Fillers, putties, plasters, modelling clay

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

Conditions of use According to directions for use.

Duration and frequency Frequency of use:

Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

Physical state Fluid

Concentration of the substance in the mixture Raw material.

Other operational conditions

Other operational conditions affecting environmental exposure

No special measures required.

Use only on hard ground.

Other operational conditions affecting worker exposure

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Other operational conditions affecting consumer exposure No special measures required.

Other operational conditions affecting consumer exposure during the use of the product Not applicable.

Risk management measures

Worker protection

Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaust or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Use product only in enclosed systems.

Personal protective measures Do not inhale gases / fumes / aerosols.

Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

Environmental protection measures

Water

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Do not allow to reach sewage system.

Soil

The product is only processed over the concrete collecting basin.

Prevent contamination of soil.

Disposal measures Ensure that waste is collected and contained.

Disposal procedures

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Waste type Partially emptied and uncleaned packaging

Exposure estimation

Consumer

Not relevant for this Exposure Scenario.

This product is to be used by professional technicians only.

Continue on page 14

GB

Trade name: **SPRAY 900 CAVITY WAX**

Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

GB